WorkForce Enterprise WF-C21000 D4TW



With print speeds of up to 100ppm, this affordable ecoresponsible MFP offers reliability and outstanding performance

Print up to 100,000 pages in mono or 50,000 in colour without changing the supplies. This reliable, low maintenance 4-in-1 device² offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Superior quality at high speeds

The WorkForce Enterprise WF-C21000 delivers superior image quality at print speeds of up to 100ppm and a fast first copy out time (FCOT) of 4.9 seconds³. **Super high ink yield**

Print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies.¹ This means there is even less need for user intervention. Through fewer consumables and supplies, it also produces less waste. With ultra-low power consumption, the overall environmental impact of printing is cut dramatically.

Robust, high-end finishing capability

With advanced finishing such as booklet finisher and hole punch options, this device offers advanced finishing capability. It also offers a high paper capacity of up to 5,350 pages, increasing productivity further.

Heat-free technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an fast FCOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson's new Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



KEY FEATURES

- Faster performance Fast FCOT of 4.9 seconds and print speeds of up to 100ppm
- High capacity ink yield Users can print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies¹
- Improved finishing capability Robust finishing such as booklet finisher and hole punch options
- Powerful scanning capability Thin paper support and improved quality of scanning
- Works with Epson Remote Services Cloud based, advanced diagnosis of Epson printers and MFPs



TECHNOLOGY			
Printing Method	PrecisionCore™ Micro TFP printhead		
Nozzle Configuration	8,676 Nozzles Black, 8,676 Nozzles per Color		
Minimum Droplet Size	3.5 pl		
Ink Technology	DURABrite [™] Pro		
Category	Office Departmental		
All-in-One Functions	Print, Scan, Copy		
PRINT			
First Page Out	Monochrome 4.9 Seconds, Colour 4.9 Seconds		
Printing Speed ISO/IEC 2473	34 100 pages/min Monochrome, 100 pages/min Colour		
Duplex Printing Speed ISO/IEC 24734	100 A4 Pages/min Monochrome, 100 A4 Pages/min Colour		
Printing Speed ISO/IEC 2473 (A3)	34 54 pages/min Monochrome, 54 pages/min Colour		
Maximum Printing Speed	100 pages/min Monochrome (plain paper 75 g/m²), 100 pages/min Colour (plain paper 75 g/m²)		
Printing Resolution	600 x 2,400 DPI		
Printing Volume	400,000 pages per month		
	The maximum number of printed pages per month based on the performance capabilities of		
	the printer, including ISO rated print speeds and paper handling capabilities.		
Recommended Duty Cycle	8,000 - 100,000 pages per month		
Colours	Black, Cyan, Yellow, Magenta		
For detailed information on p	printing speeds please visit http://www.epson.eu/testing.		
SCAN			
Double-sided scanning	Yes		
Scanning Speed	60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided,		
	300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided, 300 dpi, ADF);		
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)		
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)		
Advanced document	Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB		
integration	Memory Device / Card		
Output formate			

WorkForce Enterprise WF-C21000 D4TW

VHAT'S IN THE BOX

Information sheet

- Power cable
- User guide

Output formats BMP, JPEG, TIFF, multi-TIFF, PDF, PNG Scanner type Contact image sensor (CIS) Optical Resolution 600 DPI x 600 DPI (Horizontal x Vertical)



60 g/m² - 350 g/m²

60 g/m² - 350 g/m²

150 80gsm

550 Sheets 5,350

4

MPT

Yes (A4/A3, plain paper)

Letter, 20 x 25 cm, HLT, User defined, SRA3

Plain Paper, Recycled Paper, Colour Paper, Letterhead

Min 55x 330 mm to Max 127x 1,200 mm

2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray

A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope),

Duplex

Compatible Paper Weight

Standard Paper input

Output Tray Capacity

Maximum paper input Number of paper trays

Paper Input Name

Compatible paper weight

Paper Formats

Custom sizes

Media type

Paper Capacity 1

SPECGROUPNAMEPAPERFEEDMPT

FAX		
Type of fax	Walk-up black and white and colour fax capability	
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page	
Error correction mode	CCITU/ITU Group3 fax with Error Correction Mode	
Fax speed dials (max)	2,000 names and numbers	
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)	
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book, Fax	
	Preview, Polling Reception	
OPY		
opy Speed	Up to 100 ipm Black, Up to 100 ipm Colour	
	*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)	
Copy resolution (dpi)	600 x 1200	
Reduction / Enlargement	25 % - 400 %	
Aximum number of copies	9,999	
aximum Copy Size	A3	
ONNECTIVITY		
letwork Printing Protocols	IPP, LDP, Port 9100, WSD	
letwork Management	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping	
rotocols		
etwork Protocol	IPv4, IPv6	
iterfaces	10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Gigabit ethernet interface, Ethernet	
	Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi	
	Direct, USB 1.1 Type A, USB 2.0 Type A, USB 3.0 Type B	
VLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)	
etwork Protocol	TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS	
APER / MEDIA HANDLING		
aper Formats	A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), Postcard, A3+, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B4	
	(25.7x36.4 cm), B5 (17.6x25.7 cm), B6 (12.5x17.6 cm), C4 (Envelope), C5 (Envelope), C6	
	(Envelope), DL (Envelope), Executive, Letter, Legal, HLT, No. 10 (Envelope), User defined	
utomatic Document Feed	150 pages	

WorkForce Enterprise WF-C21000



PAPER FEED C1	
Paper Input Name	C1
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT, Executive
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m² - 160 g/m²
Paper Capacity 1	550 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
	an a
{SPECGROUPNAMEPAPEF	-
Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m² - 160 g/m²
Paper Capacity 1	550 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
PAPER FEED LCT	
Paper Input Name	LCT
Paper Formats	A4. Letter
Compatible paper weight	60 g/m² - 160 g/m²
Paper Capacity 1	3,000 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
inoulu (Jpo	
PAPER FEED DUPLEX	
Paper Input Name	Duplex
Compatible paper weight	60 g/m² - 160 g/m²
GENERAL	
Enerav Use	170 Watt (standalone copying, ISO/IEC 24712 pattern), 1.1 Watt (sleep mode), 76 Watt
Energy Use	170 Watt (standalone copying, ISO/IEC 24712 pattern), 1.1 Watt (sleep mode), 76 Watt (Readv), 0.1 Watt (Power off). TEC 0.4 kWh/week
	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week
Supply Voltage	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz
Supply Voltage Product dimensions	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height)
Supply Voltage Product dimensions Product weight	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg
Supply Voltage Product dimensions Product weight Compatible Operating	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X
Supply Voltage Product dimensions Product weight	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit),
Supply Voltage Product dimensions Product weight Compatible Operating	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server
Supply Voltage Product dimensions Product weight Compatible Operating	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit),
Supply Voltage Product dimensions Product weight Compatible Operating	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP
Supply Voltage Product dimensions Product weight Compatible Operating Systems	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply ADDITIONAL FEATURES	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply ADDITIONAL FEATURES Features	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply ADDITIONAL FEATURES Features Panel	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply ADDITIONAL FEATURES Features Panel Media Handling	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper)
Supply Voltage Product dimensions Product weight Compatible Operating Systems Sound Power Noise Power supply ADDITIONAL FEATURES Features Panel Media Handling	 (Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 674 x 757 x 1,243 mm (Width x Depth x Height) 177.1 kg Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper) Limit access function with Epson Web Config, Secure confidential printing with PIN code

WorkForce Enterprise WF-C21000 D4TW



OTHER FEATURES Emulations

PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour

WorkForce Enterprise WF-C21000 D4TW



SUPPLIES

- WorkForce Enterprise WF-C21000 Black Ink
- WorkForce Enterprise WF-C21000 Cyan Ink
- WorkForce Enterprise WF-C21000 Magenta Ink
- WorkForce Enterprise WF-C21000 Yellow Ink
- Maintenance box
- WorkForce Enterprise Staple Cartridge for Staple Finisher C12C935401 includes 3 staple cartridges of 5000 staples for the staple finisher(C12C935501) and the booklet finisher(C12C935071
- WorkForce Enterprise Staple Cartridge for Booklet Finisher (includes 2 staple cartridges of 2000 staples for staples in the saddle unit for booklet stapling

OPTIONAL ACCESSORIES

- WorkForce Enterprise Staple Finisher C12C935501
- WorkForce Enterprise Saddle Unit C12C935801
- WorkForce Enterprise Optional Paper Guide C12C935901
- WorkForce Enterprise Finisher Bridge Unit C12C935101
- WorkForce Enterprise Booklet Finisher C12C935071
- WorkForce Enterprise 2/4 Hole Punch Unit C12C935171
- WFE Paper Feed Roller for Paper Tray C12C935941
- 3000-sheet High Capacity Paper Tray C12C933041
- Cassette Lock
- C12C933231

LOGISTICS INFORMATION

SKU	C11CH88401 C11CH88401BY
EAN code	8715946677040
Country of Origin	Indonesia



* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

WorkForce Enterprise WF-C21000 D4TW

INK YIELD DATA

C13T02Y100

C13T02Y200

C13T02Y300

C13T02Y400

C13T671300

C12C935401

C12C935411


50,000 Sayfalar

50,000

Sayfalar 50,000

Sayfalar

50,000 Sayfalar



Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

1. ¹Approx. page yield with the WF-C20600. Actual yield will vary depending on images printed and usage conditions. For more information visit

www.epson.eu/pageyield. 2. ²Fax optional in certain territories at an additional cost. Please contact your local Epson office for more information.

3. ³Approx. based on internal testing; may vary depending on the number of copies selected, the output environment, as well as the settings for size, orientation, position of paper.

